

# **Safety Data Sheet** 202

### **Section 1: Product and Company Identification**

Absolute Accuracy 4591 S Wayside Dr

Houston, TX 77087 (832) 571-2387

Product Code: 202

Synonyms: n/a

Recommended Use: CALIBRATION GAS

Usage Restrictions: INDUSTRIAL CALIBRATION GAS

### **Section 2: Hazards Identification**



Hazard Classification: Gases Under Pressure

**Hazard Statements:** 

Contains gas under pressure; may explode if heated

Toxic to aquatic life

**Precautionary Statements** 

Storage:

Protect from sunlight.
Store in well-ventilated place.

### Section 3: Composition/Information on Ingredients

	CAS#	Concentration
Hydrogen Sulfide	7783-06-4	40 PPM
Nitrogen	7727-37-9	BALANCE

	Chemical Substance	Chemical Family	Trade Names
Hydrogen Sulfide	HYDROGEN SULFIDE	Inorganic gases	HYDROGEN SULFIDE (H2S); DIHYDROGEN MONOSULFIDE; DIHYDROGEN SULFIDE; HYDROSULFURIC ACID; SULFUR DIHYDRIDE; SULFURETED HYDROGEN; SULFUR HYDRIDE; STINK DAMP; SEWER GAS; RCRA U135; UN 1053; H2S
Nitrogen	NITROGEN, COMPRESSED GAS	Inorganic gases	DIATOMIC NITROGEN; DINITROGEN; NITROGEN; NITROGEN-14; NITROGEN GAS; UN 1066; N2

# **Section 4: First Aid Measures**

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Hydroge n Sulfide	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Nitrogen	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

# **Section 5: Fire Fighting Measures**

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Hydroge n Sulfide	Let burn unless leak can be stopped immediately. Large fires: Use regular foam or flood with fine water spray.	Sulfur oxides	<ul> <li>Any self-contained breathing apparatus with a full facepiece.</li> <li>Protective material types: butyl rubber, polyvinyl chloride (PVC), neoprene</li> </ul>
Nitrogen	Non-flammable. Use suitable extinguishing media for surrounding fire. Cylinders may rupture or explode if exposed to heat.	Non-flammable	Respiratory protection may be needed for frequent or heavy exposure.

# **Section 6: Accidental Release Measures**

	Personal Precautions	Environmental Precautions	Methods for Containment
Hydrogen Sulfide	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Evacuation radius: 150 feet. For tank, rail car or tank truck: 800 meters (1/2 mile). Do not touch spilled material.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Remove sources of ignition. Reduce vapors with water spray. Do not get water directly on material.
Nitrogen	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	No significant effects from contamination expected.	Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
Hydrogen Sulfide	Collect runoff for disposal as potential hazardous waste. Dike for later disposal. Absorb with sand or other non-combustible material. Add an alkaline material (lime, crushed limestone, sodium bicarbonate, or soda ash).	Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).
Nitrogen	N/A	N/A

### **Section 7: Handling and Storage**

	Handling	Storage
Hydrogen Sulfide	Store and handle in accordance with all current regulations and standards. Protect from physical damage. Store outside or in a detached building. Store in a cool, dry place. Store in a well-ventilated area. Avoid contact with light. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Notify State Emergency Response Commission for storage or use at amounts greater than or equal to the TPQ (U.S. EPA SARA Section 302). SARA Section 303 requires facilities storing a material with a TPQ to participate in local emergency response planning (U.S. EPA 40 CFR 355.30). Keep separated from incompatible substances.	Subject to handling regulations: U.S. OSHA 29 CFR 1910.119.
Nitrogen	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.

### **Section 8: Exposure Controls/Personal Protection**

	Exposure Guidelines
Hydrogen Sulfide	HYDROGEN SULFIDE: 20 ppm OSHA ceiling 50 ppm OSHA peak 10 minute(s) (once if no other measurable exposure occurs) 10 ppm (14 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 15 ppm (21 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 10 ppm ACGIH TWA 15 ppm ACGIH STEL 10 ppm (15 mg/m3) NIOSH recommended ceiling 10 minute(s) TLV-TWA: 1ppm Upper respiratory irritation (ACGIH)
Nitrogen	NITROGEN, COMPRESSED GAS: NITROGEN: ACGIH (simple asphyxiant)

#### **Engineering Controls**

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
Hydrogen Sulfide	Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing.	Any self-contained breathing apparatus with a full facepiece.
Nitrogen	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure.

#### **General Hygiene considerations**

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

### **Section 9: Physical and Chemical Properties**

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Hydro gen Sulfide	Gas	Colorless	Colorless	N/A	Gas	Rotten egg odor	N/A
Nitrog en	Gas	Clear	Colorless	N/A	Gas	Odorless	Tasteless

	Flash Point	Flammability	Partition Coefficient	Autoignition	Upper Explosive	Lower Explosive
				Temperature	Limits	Limits
Hydro	Flammable	Not available	Not available	500 F (260 C)	45.5%	3.9%
gen						
Sulfid						
е						
Nitrog	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable
en						

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рН	Odor Threshold	Evaporation Rate	Viscosit y
Hyd rog en Sulf ide	-78 to -77 F (-61 to - 60.3 C)	-123 F (-86 C)	15200 mmHg @ 25 C	1.2 (Air=1)	1.192	2.58-2.9% @ 20 C	4.5-<7 (satur ated solutio n)	0.13 ppm	Not applicable	0.0128 cP @ 25 C
Nitr oge n	-321 F (- 196 C)	-346 F (- 210 C)	760 mmHg @ -196 C	0.967 (Air=1)	Not applicable	1.6% @ 20 C	Not applic able	Not available	Not applicable	0.01787 cP @ 27 C

_							
П	Molecular	Molecular	Density	Weight per	Volatility by	Volatility	Solvent
- 1	Willeculai	Willeculai	Delisity	weight per	V Claulity by	Volatility	JOIVEIIL
- 1	Weight	Formula	=	Gallon	Valuma	-	Solubility
	weight	Formula		Galloli	Volume		Solubility

Hydro gen Sulfid e	34.08	H2-S	1.539 g/L @ 0 C	Not available	Not available	Not applicable	Soluble: Carbon disulfide, alcohol, ether, glycerol, gasolines, kerosene, crude oil, alkali solutions
Nitrog	28.0134	N2	1.2506 g/L	Not available	100%	1	Soluble: Liquid
en							ammonia

# Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
Hydrogen Sulfide	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Combustible materials, metals, oxidizing materials, halogens, metal oxides, metal salts, bases, rust, oxidants, oxygen, copper powder, acetaldehyde, silver fulminate
Nitrogen	Stable at normal temperatures and	Stable at normal temperatures and	Metals, oxidizing materials
	pressure.	pressure.	

	Hazardous Decomposition Products	Possibility of Hazardous Reactions	
Hydrogen Sulfide	Oxides of sulfur	Will not polymerize.	
Nitrogen	Oxides of nitrogen	Will not polymerize.	

### **Section 11: Toxicology Information**

#### **Acute Effects**

	Oral LD50	Dermal LD50	Inhalation
Hydrogen Sulfide	444 ppm inhalation-rat LC50	Irritation 0.000125 ppm/5 hour(s) eyes-human	Irritation, lack of sense of smell, sensitivity to light, nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, disorientation, tremors, visual disturbances, suffocation, lung congestion, internal bleeding, heart damage, nerve damage, brain damage, coma, death
Nitrogen	Not available	Not available	Nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, tingling sensation, loss of coordination, convulsions, coma

	Eye Irritation	Skin Irritation	Sensitization
Hydrog en Sulfide	Irritation, sensitivity to light, visual disturbances	Irritation liquid: frostbite	Acute toxicity, Category 2, inhalation; H330: Fatal if inhaled. Specific Target Organ Toxicity (single exposure), Category 3; H335: May cause respiratory irritation. Hazardous to the aquatic environment, Acute Category 1; H400: Very toxic to aquatic life
Nitroge n	Contact with rapidly expanding gas may cause burns or frostbite	No information on significant adverse effects	Difficulty breathing

#### **Chronic Effects**

	Carcinogenicity	Mutagenicity	Reproductive Effects	Develop mental Effects
Hydroge n Sulfide	Not available	Not available	Available.	No data
Nitrogen	Not hazardous	Not available	Not available	No data

# **Section 12: Ecological Information**

**Fate and Transport** 

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Hydro gen Sulfide	Fish toxicity: Acute LC50 7 ug/L Fresh water Fish - Fathead minnow - Pimephales	Highly toxic to aquatic life.	Not available	Not available

	promelas - FRY 96 hours; 14.9 ug/L 96 hour(s) LC50 (Mortality) Fathead minnow (Pimeph Invertibrate toxicity: 9730 ug/L 1.5 hour(s) (Mortality) Mediterranean mussel (Mytilus galloprovincialis) Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available			
Nitrog en	Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

# **Section 13: Disposal Considerations**

Hydrogen Sulfide	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262.
	Hazardous Waste Number(s): U135.
Nitrogen	Dispose in accordance with all applicable regulations.

### **Section 14: Transportation Information**

#### U.S. DOT 49 CFR 172.101

#### **DOT Information For This Mixture**

Shipping Name	Compressed gas, n.o.s. (Nitrogen, Hydrogen Sulfide)			
UN Number	UN1956			
Hazard Class	2.2			
Hazard Information	Non-Flammable Gas			

#### **Individual Component Information**

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
H y dr o g e n S ul fi de	Hydrogen sulfide	UN1053	2.3	Not applicable	2.3; 2.1	Forbidden	Forbidden	Toxic- Inhalation Hazard Zone B

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Ni tr	Nitrogen, compressed	UN1066	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A
0	'							
g								
en	1	1	I	ĺ	l	l	l	

**Canadian Transportation of Dangerous Goods** 

	Shipping Name	UN Number	Class	Packing Group / Risk Group
Hyd	HYDROGEN SULFIDE; or	UN1053	2.3; 2.1	Not applicable
rog	HYDROGEN SULPHIDE			
en				
Sulf				
ide				
Nitr	Nitrogen, compressed	UN1066	2.2	Not applicable
oge				
n				

# Section 15: Regulatory Information

**U.S. Regulations** 

	9				
	CERCLA Sections	SARA 355.30	SARA 355.40		
Hydrog en Sulfide	100 LBS RQ	500 LBS TPQ	100 LBS RQ		
Nitroge n	Not regulated.	Not regulated.	Not regulated.		

#### **SARA 370.21**

	Acute	Chronic	Fire	Reactive	Sudden Release
Hydr	Yes	No	Yes	No	Yes
ogen					
Sulfid					
е					
Nitro	Yes	No	No	No	Yes
gen					

#### **SARA 372.65**

Hydrogen Sulfide	HYDROGEN SULFIDE: Administrative stay issued Aug. 22, 1994
Nitrogen	Not regulated.

**OSHA Process Safety** 

Hydrogen Sulfide	1500 LBS TQ
Nitrogen	Not regulated.

**State Regulations** 

	CA Proposition 65
Hydrogen Sulfide	Not regulated.
Nitrogen	Not regulated.

**Canadian Regulations** 

	WHMIS Classification
Hydrogen Sulfide	A, B1, D1A, D2B.
Nitrogen	A

**National Inventory Status** 

	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Hydro	Listed on inventory.	Not listed.	Listed on inventory.
gen			
Sulfid			

е			
Nitrog	Listed on inventory.	Not listed.	Listed on inventory.
en			

# Section 16: Other Information

NFPA Rating	
Hydrogen Sulfide	HEALTH=4 FIRE=4 REACTIVITY=0
Nitrogen	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA

<sup>0 =</sup> minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard