

Safety Data Sheet 353

Section 1: Product and Company Identification

Absolute Accuracy 4591 S Wayside Dr Houston, TX 77087 (832) 571-2387

Product Code: 353 Synonyms: N/A Recommended Use: CALIBRATION GAS Usage Restrictions: INDUSTRIAL CALIBRATION GAS

Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure

Hazard Statements: Contains gas under pressure; may explode if heated

Precautionary Statements

Storage: Protect from sunlight. Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

	CAS #	Concentration
Sulfur Dioxide	7446-09-5	10 PPM
Air	Not applicable	BALANCE

	Chemical Substance	Chemical Family	Trade Names
Sulfur Dioxide	SULFUR DIOXIDE	Inorganic gases	SULFUROUS ACID ANHYDRIDE; SULFUROUS OXIDE; SULPHUR DIOXIDE; SULFUROUS ANHYDRIDE; FERMENTICIDE LIQUID; SULFUR DIOXIDE(SO2); SULFUR OXIDE; SULFUR OXIDE(SO2); STCC 4904290; UN 1079; O2S
Air	AIR, COMPRESSED	Inorganic gases	AIR; UN 1002 Nitrogen CAS: 7727-37-9 Oxygen CAS: 7782-44-7

Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Sulfur Dioxide	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention. Thoroughly clean and dry contaminated clothing before reuse. Destroy contaminated shoes.	Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Air	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Get medical attention.	

Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Sulfur Dioxide	Non-flammable. Use suitable extinguishing media for surrounding fire.	None known	Non-flammableNon-flammable
Air	Use extinguishing agents appropriate for surrounding fire.		 No respirator is required under normal conditions of use.

Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
Sulfur Dioxide	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Evacuation radius: 150 feet.	Avoid contamination of environment.	Stop leak if possible without personal risk. Reduce vapors with water spray. Do not get water directly on material.
Air			Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
Sulfur Dioxide	Stop leak, evacuate area. Contact emergency personnel.	Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).
Air		

Section 7: Handling and Storage

	Handling	Storage
Sulfur Dioxide	Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier.
Air	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	

Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
Sulfur Dioxide	SULFUR DIOXIDE: 2 ppm (5 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 5 ppm (13 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 5 ppm (13 mg/m3) OSHA TWA 2 ppm ACGIH TWA 5 ppm ACGIH STEL 2 ppm (5 mg/m3) NIOSH recommended TWA 10 hour(s) 5 ppm (13 mg/m3) NIOSH recommended STEL
Air	AIR, COMPRESSED: No occupational exposure limits established.

Engineering Controls

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
Sulfur Dioxide	Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	For the gas: Wear appropriate chemical resistant clothing. For the liquid: Wear appropriate protective, cold insulating clothing.	Non-flammable
Air	Eye protection not required under normal conditions.	Protective clothing is not required under normal conditions.	No respirator is required under normal conditions of use.

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Sulfur Dioxid e	Gas	Clear	Colorless	N/A	Gas	Irritating odor	N/A
Air	Gas	Clear	Colorless		Gas	Not available	

	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Sulfur Dioxid e	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable
Air						

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рН	Odor Threshold	Evaporation Rate	Viscosit y
Sulf ur Dio xide	14 F (-10 C)	-99 F (-73 C)	2432 mmHg @ 20 C	2.26 (Air=1)	1.462 @ -10 C	22.8% @ 0 C	Acidic in solutio n	3-5 ppm	>1 (butyl acetate=1)	Not available
Air	-317 F (- 194 C)	Not available	760 mmHg @ -194 C	1	Not applicable	Slightly soluble	Not applic able	Not available	Not applicable	0.01853 cP @ 26.85 C

	Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
Sulfur Dioxi de	64.06	S-O2	0.169	Not available	Not available	Not applicable	Soluble: Alcohol, acetic acid, sulfuric acid, ether, chloroform, benzene, sulfuryl chloride, nitrobenzenes, toluene, acetone
Air			1.29 g/L @ 0 C			Not applicable	Slightly Soluble

Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials	
Sulfur Dioxide	Stable at normal temperatu pressure.	res and Stable at normal temperatures an pressure.	d Combustible materials, metals, bases, oxidizing materials, halogens, metal carbide, metal oxides, peroxides, reducing agents, potassium, sodium, nitryl chloride, acrolein, metal oxides, carbide	
Air	Stable at normal temperatu pressure.	res and Stable at normal temperatures an pressure.	d None known	
	Hazardous Dec	composition Products	Possibility of Hazardous Reactions	
Sulfur Diox	ide Forms sulfurous	acid solution on reaction with water.	Will not polymerize.	
Air	No hazard expe	cted.	Will not polymerize.	

Section 11: Toxicology Information

Acute Effects

	Oral LD50	Dermal LD50	Inhalation
Sulfur Dioxide	LC50, 1 hr, rat = 2520 ppm	Not available	Allergic reactions, burns, toxic
Air	Not available	Not available	

	Eye Irritation	Skin Irritation	Sensitization
Sulfur Dioxide	Corrosive, burns	Corrosive, burns	Acute toxicity, Category 3, inhalation; H331: Toxic if inhaled. Skin corrosion, Category 1B; H314: Causes severe skin burns and eye damage.
Air	No information is available	No information is available	No significant target effects reported.

Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Develop mental Effects
Sulfur Dioxide	IARC: Human Inadequate Evidence, Animal Limited Evidence, Group 3; ACGIH: A4 -Not Classifiable as a Human Carcinogen	Available.	Available.	No data
Air	Not available	Not available	No data	No data

Section 12: Ecological Information

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Sulfur Dioxid e	Fish toxicity: 3000 ug/L 0.667-0.833 hour(s) (Avoidance) Atlantic menhaden (Brevoortia tyrannus) Invertibrate toxicity: Not available Algal toxicity: 500 ug/L 6 day(s) (Cellular) Green algae (Rhizoclonium hieroglyphicum) Phyto toxicity: Not available Other toxicity: >=150 ug/L NR hour(s) (Biochemical) Duckweed (Lemna minor)	Not available	Not available	Not available
Air	Fish toxicity: Not available	Not available	Not available	Not available

Section 13: Disposal Considerations

Sulfur Dioxide	Dispose in accordance with all applicable regulations.
Air	Dispose in accordance with all applicable regulations.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

DOT Information For This Mixture

Shipping Name Compressed gas, n.o.s. (Air, Sulfur Dioxide)				
UN Number	UN1956			
Hazard Class	2.2			
Hazard Information	Non-Flammable Gas			

Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
S ul fu Di o xi de	Sulfur dioxide	UN1079	2.3	Not applicable	2.3; 8	Forbidden	Forbidden	Toxic- Inhalation Hazard Zone C
Ai r	Air, compressed	UN1002	2.2	Not available	2.2	Not available	Not available	Not available

Canadian Transportation of Dangerous Goods

	Shipping Name	UN Nu	mber	Class	Packing	g Group /	Risk Grou	р
- 1					T =			

Sulf ur Dio	Sulfur dioxide	UN1079	2.3; 8	Not applicable
xide				
Air	Air, compressed	UN1002	2.2	Not available

Section 15: Regulatory Information

U.S. Regulations

	CERCLA Sections	SARA 355.30	SARA 355.40	
Sulfur Dioxide	Not regulated.	500 LBS TPQ	500 LBS RQ	
Air	Not regulated.	Not regulated.	Not regulated.	

SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
Sulfu r Dioxi de	Yes	Yes	No	Νο	Yes
Air	No	No	No	No	Yes

SARA 372.65

Sulfur Dioxide	Not regulated.
Air	Not regulated.

OSHA Process Safety

- een an recee earery	
Sulfur Dioxide	1000 LBS TQ
Air	Not regulated.

State Regulations

	CA Proposition 65
Sulfur Dioxide	WARNING: This product can expose you to chemicals including sulfur dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.
Air	Not regulated.

Canadian Regulations

	WHMIS Classification
Sulfur Dioxide	AD1
Air	A

National Inventory Status

	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
	Listed on inventory.	Not listed.	Not determined.
Dioxid			
е			
Air	Not listed on inventory.	Not listed.	Not determined.

Section 16: Other Information

	NFPA Rating
Sulfur Dioxide	HEALTH=3 FIRE=0 REACTIVITY=0
Air	HEALTH=0 FIRE=0 REACTIVITY=0
0 - minimal hererd 1 - clight here	and 0 - mederate beyond 0 - severe beyond 1 - extreme beyond

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard